

MILANO

LED DOWNLIGHT RANGE



IP65 & IK10
model available



● 170mm

● 200mm

● 230mm

● 3000K

● 3500K

● 4000K

● Tunable white



● White trim

● Black trim

● Silver trim

IP54

5 year
Warranty

www.salcommercial.net.au

SAL | COMMERCIAL

MILANO



Milano 170

IP54

Product Range

Family	Description	Lumens	CCT	Beam	Trim	Code
170mm	20w recessed LED downlight	1350lm	3000K	24°	white	DML172030N24WH
170mm	20w recessed LED downlight	1350lm	3000K	40°	white	DML172030N40WH
170mm	20w recessed LED downlight	1350lm	3000K	60°	white	*DML172030NWH
170mm	20w recessed LED downlight	1400lm	3500K	24°	white	DML172035N24WH
170mm	20w recessed LED downlight	1400lm	3500K	40°	white	DML172035N40W
170mm	20w recessed LED downlight	1400lm	3500K	60°	white	*DML172035NWH
170mm	20w recessed LED downlight	1500lm	4000K	24°	white	DML172040N24WH
170mm	20w recessed LED downlight	1500lm	4000K	40°	white	DML172040N40WH
170mm	20w recessed LED downlight	1500lm	4000K	60°	white	*DML172040NWH

*applies to standard code methodology



Milano 200

IP54

Family	Description	Lumens	CCT	Beam	Trim	Code
200mm	30w recessed LED downlight	2600lm	3000K	60°	white	DML203030NWH
200mm	30w recessed LED downlight	2750lm	3500K	60°	white	DML203035NWH
200mm	30w recessed LED downlight	2900lm	4000K	60°	white	DML203040NWH



Milano 230

IP54

Family	Description	Lumens	CCT	Beam	Trim	Code
230mm	40w recessed LED downlight	3600lm	3000K	60°	white	DML203030NWH
230mm	40w recessed LED downlight	3800lm	3500K	60°	white	DML203035NWH
230mm	40w recessed LED downlight	4000lm	4000K	60°	white	DML203040NWH



Milano 200 KP

IP65

IK10

Family	Description	Lumens	CCT	Beam	Trim	Code
200mm	30w recessed LED downlight IK10 IP65	2600lm	3000K	60°	white	DML203030NWHKP
200mm	30w recessed LED downlight IK10 IP65	2750lm	3500K	60°	white	DML203035NWHKP
200mm	30w recessed LED downlight IK10 IP65	2900lm	4000K	60°	white	DML203040NWHKP

Code methodology

Family	Size	Wattage	CCT	Dimming type	Beam	CRI	Trim
DML <small>(Downlight Milano)</small>	17 (170mm)	10/15/20*	30 3000K	N* Non-dim	24°/40°/*60° <small>(170mm only)</small>	C8*	WH* White
	20 (200mm)	14/18/25/30*	35 3500K	DT DALI2		C9**	BK Black
	23 (230mm)	18/25/30/40*	40 4000K	TW (Tunable white)	*60° <small>(200mm 230mm)</small>		SL Silver

*applies to standard code methodology - 170mm

**applies to standard code methodology - 200/230mm