

AUSTIN

HIGH POWER LED FLOODLIGHT

75w
to
1200w

12,000lm
to
208,000lm

High Efficiency
160lm/w

5 Year
Warranty

www.salcommercial.net.au

SAL | COMMERCIAL

AUSTIN

75/100w

Description	Lumens	CCT	CRI	Beam	Code
Austin LED floodlight	13,000lm	4000K	70	See code methodology below for available options	FAN7540N*
Austin LED floodlight	18,000lm	4000K	70	See code methodology below for available options	FAN10040N*

150/200w

Austin LED floodlight	25,000lm	4000K	70	See code methodology below for available options	FAN15040N*
Austin LED floodlight	36,000lm	4000K	70	See code methodology below for available options	FAN20040N*

300w

Austin LED floodlight	52,000lm	4000K	70	See code methodology below for available options	FAN30040N*
-----------------------	----------	-------	----	--	------------

400w

Austin LED floodlight	72,000lm	4000K	70	See code methodology below for available options	FAN40040N*
-----------------------	----------	-------	----	--	------------

600w

Austin LED floodlight	105,000lm	4000K	70	See code methodology below for available options	FAN60040N*
-----------------------	-----------	-------	----	--	------------

800w

Austin LED floodlight	144,000lm	4000K	70	See code methodology below for available options	FAN80040N*
-----------------------	-----------	-------	----	--	------------

1200w

Austin LED floodlight	208,000lm	4000K	70	See code methodology below for available options	FAN120040N*
-----------------------	-----------	-------	----	--	-------------

CODE METHODOLOGY

Family	Wattage	CCT	Dimming	Beam (°)
FAN (Floodlight - Austin)	75/100/150/ 200/300/400/ 600/800/1200	40 4000K 50 5000K	D DALI *Non-dimmable supplied as standard	S1/2/3 *20° / 30° / 60° T1/2/3/4/5 Type I / II / III / IV / V

*select required beam type to complete product code

PRODUCT FEATURES

- 160lm/w efficiency
- IP65 ingress protection
- Galvanised steel trunnion arm
- UV stabilised polycarbonate diffuser
- Large range of optics available
- CRI80 available
- DALI dimming driver optional

KEY APPLICATIONS

- Industrial area lighting
- General purpose floodlighting

75w
to
1200w

12,000lm
to
208,000lm

High Efficiency
160lm/w

5 Year
Warranty