SAL COMMERCIAL

DML111240DWHKP

Downlights

Milano KP

110mm Recessed IP65 IK10 Commercial LED Downlight

UGR <19 | IK10 | IP65 | DALI-2 AVAILABLE | 5 YEAR WARRANTY

Features

- Die-cast aluminium body for efficient heat dissipation
- High efficacy LED technology 100lm/W
- Excellent glare control with set back optical design
- Quick release mounting clips for easy installation or maintenance

Polar curve



Dimensions



Cutout: 100mm

Technical Specifications

Light Source	High performance SMD
Correlated colour temp.	4000K
MacAdam Step (SDCM)	≤3 MacAdam
Light Distribution	60°
Unified Glare Rating	*UGR <19
Lumen Output	1100lm
Cyanosis Compliance	N/A
Colour rendering index	Ra≥90, R9≥50
Lumen maintenance	L90 B10 >50,000 hours
Trim colour	White
Mounting	Recessed
Diffuser type	Polycarbonate
Ingress protection	IP65
Rated supply voltage	220-240V AC
Mains frequency	50 Hz
Driver type	DALI-2 remote constant current

Order Code: DML111240DWHKP

FAMILY	Size	Wattage	CCT	Driver Type	Finish	Special
DML Downlight MiLano	**11** 110mm	**12** 8 / 800lm	**40** 3000	**D** Non dim	**WH** WHite trim	**KP** IK10 / IP65
		12 / 1100lm	3500	Phase dim	BlacK trim	
			4000	DALI-2		
			Tuneable White			
			CYanosis Compliant			
			RGBW			

*The maximum UGR rating of the product is UGR 19 as per CIE UGR tables for standardized conditions based on fixed room sizes and specific room surface reflectance combinations.

SAL Commercial +61 2 8717 4320
sales@salcommercial.net.au
quotations@salcommercial.net.au
Servicing QLD / NSW-ACT / VIC-TAS / SA-NT / WA / NZ

PDF Prepared: 30.06.2026 11:13am
Last page update: Jun 2026
© Copyright SAL Commercial - All Rights Reserved