SAL COMMERCIAL

DMLS202540DWH

Downlights

Milano S

200mm Surface Mount Commercial LED Downlight

UGR <19 | IK08 | IP65 | DALI-2 AVAILABLE | 5 YEAR WARRANTY

Features

- Die-cast aluminium body for efficient heat dissipation
- High efficacy LED technology 100lm/W
- Excellent glare control with set back optical design
- Extruded aluminium body finished in durable powdercoated White or Black finish

Polar curve



Dimensions



Technical Specifications

Light Source	High performance SMD
Correlated colour temp.	4000K
MacAdam Step (SDCM)	≤3 MacAdam
Light Distribution	60°
Unified Glare Rating	*UGR <19
Lumen Output	2400lm
Cyanosis Compliance	N/A
Colour rendering index	Ra≥90, R9≥50
Lumen maintenance	L90 B10 >50,000 hours
Trim colour	White
Mounting	Recessed
Diffuser type	Polycarbonate
Ingress protection	IP65
Rated supply voltage	220-240V AC
Mains frequency	50 Hz
Driver type	DALI-2 integral constant current

Order Code: DMLS202540DWH

FAMILY		Size		Wattage		CCT		Driver Type		Finish	
DMLS	**D**ownlight **MiL**ano **S**urface	20	200mm	25	**15** / 1500lm	40	3000	D	**N**on dim	WH	**WH**ite trim
					20 / 1900lm		3500		**P**hase dim		Blac**K** trim
					25 / 2400lm		4000		DALI-2		
					30 / 2900lm		Tuneable **W**hite				
							CYanosis Compliant				
							RGBW				

*The maximum UGR rating of the product is UGR 19 as per CIE UGR tables for standardized conditions based on fixed room sizes and specific room surface reflectance combinations.

SAL Commercial +61 2 8717 4320
sales@salcommercial.net.au
quotations@salcommercial.net.au
Servicing QLD / NSW-ACT / VIC-TAS / SA-NT / WA / NZ

PDF Prepared: 30.06.2026 11:13am
Last page update: Jun 2026
© Copyright SAL Commercial - All Rights Reserved